



Xenon Beacon (Strobe) 12/24V DC - Base Only - No Lens. 10 Joule Light Energy @ 60 Flashes Per Minute, 7.5 Joule Light Energy @ 90 Flashes Per Minute

- Complete visual signalling range from high efficiency static or flashing LED's to high discharge Xenon beacons to rotating parabolic reflector beacons, we have the solution suitable for your application.
- Available in a variety of frame sizes and with accessories such as protective cages and brackets to cater to your mounting requirements.
- Multiple colour varieties available including Red, Green, Amber and Blue to convey whichever message is required.

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	X400 / 401
Indication Mode(s)	Sight
Lamp Type	Xenon type
Illumination Mode	Flashing
Speed, Flash	90 per min
Un, Nominal Operational Voltage(s), DC	12 V DC 24
Ie, Current, Operational, 12V DC	1.45 A@12VDC
Ie, Current, Operational, 24V DC	0.7 A@24VDC
Details, Current	1.45/0.7A
Material, Base	ABS (Acrylonitrile Butadiene Styrene) - UV Stabilised
Colour, Base	Black base
Connection / Termination	Fixed (non-removable) Terminal Block
Number of Terminals	2 qty
Mounting, Terminal Block	Internal Mount
IP Rating	IP65
Mounting (Multiple)	Surface Mount Wall Mount
Height	205 mm
Width	115 mm
Depth	115 mm
Weight	0.82 kg
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	55 °C max
Certifications	CE RoHS

Catalogue No: **MOX401-18**

BEACON XENON STROBE 10/7.5J 12/24V DC BASE

Signalling Devices > Sight Indication > Beacons > Moflash Beacons > Xenon Beacons > MOX400/401 Series - Xenon Beacons



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	MOX401-18_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	MOX401-18_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	MOX401-18_Manufacturer Catalogue

