


# Catalogue No: **SLBM633PD**

## LOAD BREAK SWITCH SLBM 3P 63A DIRECT HANDLE KIT

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Socomec Load Break Switches > Socomec SLBM - Standard Load Break Modular Series (16A to 125A) > SLBM Switch - Supplied with Direct Mount Handle



Representative Photo Only  
(actual product may vary based on configuration selections)

### SLB KIT 63A 3P DIRECT HDL

- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

### SPECIFICATIONS

Product Series	SLB
Number of Poles	3
Icw, Short Time Withstand Current, 300ms (rms)	3 kA, 300ms
Ui, Rated Insulation Voltage	800 V (rms)
Uimp, Impulse Withstand Voltage	8 kV
Ith, Thermal Current at 40°C	63 A
Ie, Rated Operational Current, AC-20a, 415V	63 A@415V
Ie, Rated Operational Current, AC-20a, 500V	63 A@500V
Ie, Rated Operational Current, AC-20a, 690V	63 A@690V
Ie, Rated Operational Current, AC-20b, 415V	63 A@415V
Ie, Rated Operational Current, AC-20b, 500V	63 A@500V
Ie, Rated Operational Current, AC-20b, 690V	63 A@690V
Ie, Rated Operational Current, AC-21a, 400V	63 A@400V
Ie, Rated Operational Current, AC-21a, 415V	63 A@415V
Ie, Rated Operational Current, AC-21a, 500V	63 A@500V
Ie, Rated Operational Current, AC-21a, 690V	63 A@690V
Ie, Rated Operational Current, AC-21b, 415V	63 A@415V
Ie, Rated Operational Current, AC-21b, 500V	63 A@500V
Ie, Rated Operational Current, AC-21b, 690V	63 A@690V
Ie, Rated Operational Current, AC-22a, 400V	63 A@400V
Ie, Rated Operational Current, AC-22a, 415V	63 A@415V
Ie, Rated Operational Current, AC-22a, 500V	63 A@500V
Ie, Rated Operational Current, AC-22a, 690V	40 A@690V
Ie, Rated Operational Current, AC-22b, 415V	63 A@415V
Ie, Rated Operational Current, AC-22b, 500V	63 A@500V
Ie, Rated Operational Current, AC-22b, 690V	63 A@690V
Ie, Rated Operational Current, AC-23a, 400V	63 A@400V
Ie, Rated Operational Current, AC-23a, 415V	63 A@415V

# Catalogue No: **SLBM633PD**

## LOAD BREAK SWITCH SLBM 3P 63A DIRECT HANDLE KIT

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Socomec Load Break Switches > Socomec SLBM - Standard Load Break Modular Series (16A to 125A) > SLBM Switch - Supplied with Direct Mount Handle



le, Rated Operational Current, AC-23a, 500V	63 A@500V
le, Rated Operational Current, AC-23a, 690V	40 A@690V
le, Rated Operational Current, AC-23b, 415V	63 A@415V
le, Rated Operational Current, AC-23b, 500V	63 A@500V
le, Rated Operational Current, AC-23b, 690V	40 A@690V
le, Rated Operational Current, DC-20a, 110V	63 A@110V
le, Rated Operational Current, DC-20a, 250V	63 A@250V
le, Rated Operational Current, DC-20a, 400V	63 A@400V
le, Rated Operational Current, DC-20b, 110V	63 A@110V
le, Rated Operational Current, DC-20b, 250V	63 A@250V
le, Rated Operational Current, DC-20b, 400V	63 A@400V
le, Rated Operational Current, DC-21a, 110V	63 A@110V
le, Rated Operational Current, DC-21a, 250V	63 A@250V
le, Rated Operational Current, DC-21a, 400V	40 A@400V
le, Rated Operational Current, DC-21b, 110V	63 A@110V
le, Rated Operational Current, DC-21b, 250V	63 A@250V
Im, Rated Make/Break Capacity, 4-Pole, DC-21b, 400V	40 A 4P@400V
kW Rating, AC-23a, 415V, 3ph	30 kW @415V
Cable Cross Section (Min)	2.5 mm <sup>2</sup> mm
Cable Cross Section (Max)	35 mm <sup>2</sup> mm
Tightening Torque, Min	3.5 Nm
Tightening Torque, Max	3.85 Nm
Height	85 mm
Width	52.5 mm
Depth	75 mm
Weight	0.26 kg
Mechanical Service Life	100000 cycles

### REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

# Catalogue No: **SLBM633PD**


## LOAD BREAK SWITCH SLBM 3P 63A DIRECT HANDLE KIT

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Socomec Load Break Switches > Socomec SLBM - Standard Load Break Modular Series (16A to 125A) > SLBM Switch - Supplied with Direct Mount Handle




### SIRCO M 16 to 80 A


Direct operation with handle



External front operation



External side operation



Rating (A)	D min.	Overall dimensions			Terminal shrouds		Switch body			Switch mounting		Connection terminals
		D max.	E min.	E max.	AC	F	F1	G	J	M	N	T
16...40	30	235	100	372	110	45	15	68	15	30	75	15
63...80	30	235	100	372	110	52.5	17.5	76	17.5	35	85	17.5

Dimension Diagram

