Catalogue No: **TDGB2**

ELR TOROID CLOSED CORE 2 WIRE 35mm min 30mA

Power Distribution and Protection > Earth Leakage Protection > Earth Leakage Relays > IME Earth Leakage Relays and Toroids > 2 Wire Toroid > TDG Series - Closed Core Toroid





Earth Leakage Toroid 2 wire to suit RD relay. 35mm internal diameter

- Suits RD Series Earth Leakage Relays
- Internal diameter 28-310 mm
- Closed core and split core models

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS					
Product Series	TD				
Component Type Power Distribution & Protection	Toroid				
Component Type Transformer	Closed-core Transformer				
Details, Transformer	Suits RD range of earth leakage relays				
le, Rated Operational Current, nom	70 A,nom				
le, Rated Operational Current, max	420 A,max				
IΔn, Leakage Current, Min	30 mA				
Ith, Thermal Current, Short Time, 1s	20 kA				
ldyn, Current, Dynamic	40kA/ 0.05s				
Diameter, Internal	35 mm				
Ui, Rated Insulation Voltage	720 V (rms)				
Mounting	Screw Fixing				
Material, Body / Housing	ABS Self extinguishing material				
Terminal Type	Screw Terminal(s)				
Operating Temperature, Min	-10 °C min				
Operating Temperature, Max	55 °C max				
Storage Temperature, Min	-40 °C min				
Storage Temperature, Max	70 °C max				
Details, Primary Circuit	Supply conductors to be protected pass through toroid hole				
le, Rated Operational Current, nom	70 A,nom				
Humidity Type	Suitable for tropical enviroments				
Standards Compliance	IEC 60755 IEC 60947-2 EN 60947-2				
Sealable	Yes				
Width	92 mm				
Height	113 mm				
Depth	56 mm				
Weight	0.25 kg				




Catalogue No: **TDGB2**


ELR TOROID CLOSED CORE 2 WIRE 35mm min 30mA

Power Distribution and Protection > Earth Leakage Protection > Earth Leakage Relays > IME Earth Leakage Relays and Toroids > 2 Wire Toroid > TDG Series - Closed Core Toroid



REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-





Model	Α	В	С	D	Е	Weight
TDGB2	35	92	113	36	56	250g
TDGH2	60	105	138	36	56	300g
TDGC2	80	125	160	36	56	350g
TDGD2	110	165	198	36	56	500g
TDGE2	140	200	234	36	56	700g
TDGF2	210	290	323	44	64	1200g

Dimension Diagram



Catalogue No: **TDGB2**

ELR TOROID CLOSED CORE 2 WIRE 35mm min 30mA

Power Distribution and Protection > Earth Leakage Protection > Earth Leakage Relays > IME Earth Leakage Relays and Toroids > 2 Wire Toroid > TDG Series - Closed Core Toroid



