Catalogue No: TDGC2

ELR TOROID CLOSED CORE 2 WIRE 80mm min 30mA

Power Distribution and Protection > Earth Leakage Protection > Earth Leakage Relays > IME Earth Leakage Relays and Toroids > 2 Wire Toroid > TDG Series - Closed Core Toroid





Earth Leakage Toroid 2 wire to suit RD relay. 80mm internal diameter

- Suits RD Series Earth Leakage Relays
- Internal diameter 28-310 mm
- Closed core and split core models

Representative Photo Only (actual product may vary based on configuration selections)


| SPECIFICATIONS | |
|--|--|
| Product Series | TD |
| Component Type Power Distribution & Protection | Toroid |
| Component Type Transformer | Closed-core Transformer |
| Details, Transformer | Suits RD range of earth leakage relays |
| le, Rated Operational Current, nom | 170 A,nom |
| le, Rated Operational Current, max | 1020 A,max |
| I∆n, Leakage Current, Min | 50 mA |
| Ith, Thermal Current, Short Time, 1s | 20 kA |
| Idyn, Current, Dynamic | 40kA/ 0.05s |
| Diameter, Internal | 80 mm |
| Ui, Rated Insulation Voltage | 720 V (rms) |
| Mounting | Screw Fixing |
| Material, Body / Housing | ABS Self extinguishing material |
| Terminal Type | Screw Terminal(s) |
| Operating Temperature, Min | -10 °C min |
| Operating Temperature, Max | 55 °C max |
| Storage Temperature, Min | -40 °C min |
| Storage Temperature, Max | 70 °C max |
| Details, Primary Circuit | Supply conductors to be protected pass through toroid hole |
| le, Rated Operational Current, nom | 170 A,nom |
| Humidity Type | Suitable for tropical enviroments |
| Height | 160 mm |
| Standards Compliance | IEC 60755 IEC 60947-2 EN 60947-2 |
| Sealable | Yes |
| Width | 125 mm |
| Depth | 56 mm |
| Weight | 0.35 kg |





Catalogue No: TDGC2

ELR TOROID CLOSED CORE 2 WIRE 80mm min 30mA

Power Distribution and Protection > Earth Leakage Protection > Earth Leakage Relays > IME Earth Leakage Relays and Toroids > 2 Wire Toroid > TDG Series - Closed Core Toroid







| Model | Α | В | С | D | Е | Weight |
|-------|-----|-----|-----|----|----|--------|
| TDGB2 | 35 | 92 | 113 | 36 | 56 | 250g |
| TDGH2 | 60 | 105 | 138 | 36 | 56 | 300g |
| TDGC2 | 80 | 125 | 160 | 36 | 56 | 350g |
| TDGD2 | 110 | 165 | 198 | 36 | 56 | 500g |
| TDGE2 | 140 | 200 | 234 | 36 | 56 | 700g |
| TDGF2 | 210 | 290 | 323 | 44 | 64 | 1200g |

Dimension Diagram



Catalogue No: TDGC2

ELR TOROID CLOSED CORE 2 WIRE 80mm min 30mA

Power Distribution and Protection > Earth Leakage Protection > Earth Leakage Relays > IME Earth Leakage Relays and Toroids > 2 Wire Toroid > TDG Series - Closed Core Toroid



