Catalogue No: TOH150

MLT TAP 415/240 - 24/12 150VA

Power Distribution and Protection > Power Supplies and Transformers > Transformers > NHP Control Transformers > Multi-Tapped Control Transformers





Multi tap transformer, 150 VA, 415/240 V AC dual input, 24/12 V AC dual output

- Voltage compensation (+5/-5%) available on secondary terminals
- Isolation between primary and secondary windings
- Insulation Class F (155°C)
- Low magnetic stray field and high efficiency

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Transformer	Multi-tapped Transformer		
Input Voltage(s), AC	240 V AC 415		
Output Voltage(s), AC	12 V AC 24		
Transformer Type	Multi-tapped Transformer		
VA Rating	150 VA		
Height	102 mm		
Width	95 mm		
Depth	88 mm		
Insulation Class	F		
Voltage Tolerance on Terminals	5 +-%		
Standards Compliance	AS/NZS 61558		
REFERENCES			
IECEx Certificate -			
Supplier Declaration of Conformity:			
Installation Guide: -			
User Manual: -			



Manufacturer Datasheet:

Manufacturer Catalogue
& Product Selection:

Catalogue No: **TOH150**


MLT TAP 415/240 - 24/12 150VA


Power Distribution and Protection > Power Supplies and Transformers > Transformers > NHP Control Transformers > Multi-Tapped Control Transformers



Rating (VA)	Dimen L	sions (W	mm) M	Dual input voltage(V)	Dual output voltage (V)	Cat. No.
40	76.5	72	91	415 / 240	24 / 12	T0H40
63	76.5	94	91	415 / 240	24 / 12	T0H63
100	101	81	110	415 / 240	24 / 12	T0H100
150	101	96	110	415 / 240	24 / 12	T0H150
400	119	103	126	415 / 240	24 / 12	T0H400

Dimensions (mm)





Dimension Diagram