

Black 3/1 medium wall glue lined heat-shrink tubing 10/3 mm 4 ft



Characteristics

Wall Ø before shrinking (mm) : 10
Wall Ø after shrinking (mm) : 3

GENERAL INFORMATION

Description

Medium wall 3/1 heat-shrink tubing with adhesive.

Technical details

Medium wall, 3/1 shrinkage in length 1.2 meter.
Heat-shrink tubing in polyolefin with hot melt adhesive.
Flame retardant: outer jacket layer.
Working temperature: -45 °C to +125 °C.
Shrink temperature: 125 °C.
Dielectric strength (IEC 243): 20 kV/mm.
Tensile strength: 10.4 Mpa.
Rate voltage: 600 V.
Self-extinguishing in accordance with UL224.
Color: black.

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 1
Length (cm) : 120
Depth (cm) : 1
Net weight (kg) : 0.04
Gross weight (kg) : 0.05



Outer package 1



Bag

Height (cm) : 7.5
Length (cm) : 120
Depth (cm) : 1.5
Net weight (kg) : 0.4
Gross weight (kg) : 0.5



Outer package 2



Carton box

Height (cm) : 16
Length (cm) : 130
Depth (cm) : 20.5
Net weight (kg) : 6.48
Gross weight (kg) : 7.48



Outer package 3



Pallet

Height (cm) : 115
Length (cm) : 130
Depth (cm) : 80
Net weight (kg) : 181.4
Gross weight (kg) : 119.7

