

# Black 3/1 medium wall glue lined heat-shrink tubing 28/9 mm 4 ft



## Characteristics

Wall Ø before shrinking (mm) : 28  
Wall Ø after shrinking (mm) : 9

## GENERAL INFORMATION

### Description

Medium wall 3/1 heat-shrink tubing with adhesive.

### Technical details

Medium wall, 3/1 shrinkage in length 1.2 meter.  
Heat-shrink tubing in polyolefin with hot melt adhesive.  
Flame retardant: outer jacket layer.  
Working temperature: -45 °C to +125 °C.  
Shrink temperature: 125 °C.  
Dielectric strength (IEC 243): 20 kV/mm.  
Tensile strength: 10.4 Mpa.  
Rate voltage: 600 V.  
Self-extinguishing in accordance with UL224.  
Color: black.

### Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

## LOGISTIC INFORMATION

### Packaging



#### No packaging

Height (cm) : 2.8  
Length (cm) : 120  
Depth (cm) : 2.8  
Net weight (kg) : 0.14  
Gross weight (kg) : 0.16



### Outer package 1



#### Bag

Height (cm) : 16  
Length (cm) : 120  
Depth (cm) : 4.2  
Net weight (kg) : 1.4  
Gross weight (kg) : 1.6

x 10



### Outer package 2



#### Carton box

Height (cm) : 16  
Length (cm) : 130  
Depth (cm) : 20.5  
Net weight (kg) : 6.8  
Gross weight (kg) : 7.8



x 50

### Outer package 3



#### Pallet

Height (cm) : 115  
Length (cm) : 130  
Depth (cm) : 80  
Net weight (kg) : 190.4  
Gross weight (kg) : 39

x 1400

