

black 3/1 Medium wall glue lined heat-shrink tubing 52/16 mm 4 ft



Characteristics

Wall Ø before shrinking (mm) : **52**
Wall Ø after shrinking (mm) : **16**

GENERAL INFORMATION

Description

Medium wall 3/1 heat-shrink tubing with adhesive.

Technical details

Medium wall, 3/1 shrinkage in length 1.2 meter.
Heat-shrink tubing in polyolefin with hot melt adhesive.
Flame retardant: outer jacket layer.
Working temperature: -45 °C to +125 °C.
Shrink temperature: 125 °C.
Dielectric strength (IEC 243): 20 kV/mm.
Tensile strength: 10.4 Mpa.
Rate voltage: 600 V.
Self-extinguishing in accordance with UL224.
Color: black.

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 2.6
Length (cm) : 120
Depth (cm) : 7.8
Net weight (kg) : 0.17
Gross weight (kg) : 0.19



Outer package 1



Bag

Height (cm) : 16
Length (cm) : 120
Depth (cm) : 7.8
Net weight (kg) : 1.7
Gross weight (kg) : 1.9

x 10



Outer package 2



Carton box

Height (cm) : 16
Length (cm) : 130
Depth (cm) : 20.5
Net weight (kg) : 6.6
Gross weight (kg) : 7.6



x 40

Outer package 3



Pallet

Height (cm) : 115
Length (cm) : 130
Depth (cm) : 80
Net weight (kg) : 79.2
Gross weight (kg) : 30.4

x 480

