



Representative Photo Only
(actual product may vary based on configuration selections)

Spitfire Dual LED Weather Proof Surface Mount

- Compliance to latest ASNZS2293.3:2018.
- Reliable Stanilite Brand.
- Hi-temp NiCad batteries.

SPECIFICATIONS

Component Type Emergency Lighting	Spitfire
Testing System	Single Point Unit
Operating Mode	Non-Maintained
Operating Voltage	240 VAC
Power Consumption	1.0 W
Mounting	Surface - Ceiling
LED Life	100,000 hours
Photometric Classification	C0:D63 C90:D63
Battery Type	Ni-Cd
Height	130 mm
Width	188 mm
Depth	278 mm
Base Colour	Grey
Battery Replacement	0301220
IP Rating	IP67
Standards Compliance	ASNZS CISPR 15 ASNZS2293.3:2018 ASNZS60598.1:2017 ASNZS60598.2.22:2005

Catalogue No: **SFBWP2LED**

SPITFIRE DUAL LED WEATHER PROOF SURFACE MOUNT

Stanilite Emergency and Exit Lighting > Signature > Single Point Signature > Signature Spitfire EM



REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	Spitfire Weatherproof Emergency, NiCad or LifePO4 Battery_Supplier Declaration of Conformity (SDoC)
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-