

TECHNICAL DATA SHEET



CRC Industries (Aust) Pty Ltd

I. Product Description

CRC 5-56 Marine (formerly CRC Marine 66) is a multi-purpose oil designed to prevent damage due to water and salt atmosphere in marine engines and boating equipment. It forms a thin film that lubricates moving parts for smooth action and protects metals from corrosion caused by humidity and salt air for extended periods. Superior penetrating power breaks through rust and corrosion, loosens rusted parts and keeps them free, displaces moisture out of ignition systems to help start wet engines.

CRC 5-56 Marine increases life span, decreases maintenance and assures improved performance of all marine inboard or outboard motors.

It is safe for all metals and alloys and on most painted surfaces, coatings, plastics and rubbers.

2. Features & Benefits

- **Multipurpose oil for the protection of marine engines and boating equipment.**
- **Lubricants for smooth action** – Silences annoying squeaks and squeals.
- **Corrosion protection.**
- **Penetrates quickly** – Breaks away rust and corrosion, frees components bonded by dirt and scale.
- **Eliminates the need for many disassembly operations.**
- **Protective film** – Ongoing protection against water and salt atmosphere.
- **Displaces moisture to help start wet engines.**
- **Preventative maintenance programs** – To increase life expectancy of mechanical equipment.
- **Safe of all metal and alloys, most painted surfaces, coatings, plastics and rubbers.**
- **Contains no silicone.**
- **Cleans grease and tar off painted surfaces.**

3. Physical Properties without propellant

| | |
|--------------------|-----------------------|
| Flash Point | >60°C |
| Odour | Pleasant |
| Appearance | Straw Coloured Liquid |
| Propellant | Hydrocarbon |

Product No. 6006

4. Performance Characteristics

| | |
|--------------|----------------------|
| Type of Film | Thin Penetrating Oil |
| Dry Time | Non-Drying |

5. Package Description

| | |
|--------------------|---------------------|
| Part Number | Aerosol Size |
| 6006 | 300g |

6. Disposal

Disposal requirements vary by state and local regulations. All used and unused product should be disposed of in conformance with local, state and commonwealth laws and regulations.

7. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapour and spray mist. Avoid contact with the skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

PRODUCT WARRANTY: CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

| |
|--|
| DISCLAIMER: All information on this data sheet is based on testing by CRC Industries (Aust.) Pty. Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust.) Pty. Ltd. makes no representations or warranties of any kind concerning this data. |
|--|

TDS Version 07/2022