# TECHNICAL DATA SHEET

Product No. 6028



# **CRC Industries (Aust) Pty. Limited**

PO Box 199, Castle Hill, NSW 1765.

# I. Product Description

**CRC Tackle Guard** is a specifically formulated for the use on all tackle. **CRC Tackle Guard** is ideal for protecting and lubricating whilst with its superior penetrating power drives out moisture leaving a long lasting film that will not dry out. Protects all types of fresh and salt water reels with out damaging monofilament, EVA grips, seals etc, against corrosion.

# II. Applications

- Penetrates Drives out moisture leaving a long lasting film that will not dry out.
- ➤ Preventative maintenance programs A light spray once a day during fishing is recommended. At the end of the season or earlier if heavy use or continuous exposure to the elements occurs reels should be taken apart, cleaned and lubed, then liberally sprayed with CRC Tackle Guard.
- ➤ Environmental Shield Eliminates breakdowns due to poor environmental exposure, such as high humidity, salt air etc. deposits a molecular film on metals to protect against corrosion induced by humidity and other corrosive atmospheres.

#### III. Features & Benefits

- 1. A moisture eliminator for wet equipment.
- 2. A moisture barrier to prevent trouble before it starts.
- 3. Protective film seals out moisture.
- 4. A lubricant –will give lubrication where it penetrates, restoring smooth action and silencing annoying squeaks and squeals.
- 5. Contains no silicone.
- 6. A penetrant helps frees rusted or corroded parts.
- 7. Protects against corrosion.

# **Physical Properties without propellant**

Flash Point	79°C T.C.C.	<b>Boiling Point</b>	193°C Initial
Odour	Pleasant	% Volatile	82%
Appearance	Amber Liquid	Specific Gravity	0.81
Viscosity	4cP @ 20°C	Propellant	Hydrocarbon

### IV. Specification and Approvals

#### V. Performance Characteristics

Type of Film	Continuous molecular, self repairing film	
Expected Coverage	90 –100 m <sup>2</sup> /1 Litre	

#### VI. Directions

- Always read the entire label before using product.
- Protect eyes, skin and do not inhale. Refer to MSDS.
- Do NOT use on energised equipment.
- Spray light even coat to protect surfaces and seal out moisture. A light spray once a day is recommended.
- At end of season or earlier as required reels should be taken apart, cleaned and lubed, then liberally sprayed with **CRC Tackle Guard**.
- Apply liberally to loosen rusted/seized parts; full penetration may require several hours.
- ➤ To displace water, spray wet surfaces until run-off is clear.
- Do NOT use on energised equipment; use only in well ventilated area. Allow solvent to evaporate before energising (up to four hours, depending on surface condition and environment).

# VII. Disposal

Disposal requirements vary by state and local regulations. All used and unused product should be disposed of in conformance with local, state and commonwealth laws and regulations.

# VIII. Special Use Warnings

#### **Aerosol Cans**

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

#### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapour and spray mist. Avoid contact with the skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**PRODUCT WARRANTY:** CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

<u>DISCLAIMER</u>: All information on this data sheet is based on testing by CRC Industries (Aust.) Pty. Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust.) Pty. Ltd. makes no representations or warranties of any kind concerning this data.