

# Underground marking tape warning buried communications below white 100 m x 150 mm x 0.08 mm AU



## Characteristics

Colour : **White**  
 Text : **WARNING WARNING WARNING COMMUNICATIONS CABLE BELOW**  
 Length (m) : **100**  
 Width (mm) : **150**  
 Thickness (mm) : **0.08**  
 Material : **Polyethylene**

## Norms

> ISO 6383-12015 /  
 ASTM D882-12

## GENERAL INFORMATION

### Description

Non detectable underground tape.

### Technical details

Core inside Ø: 76 mm.

#### Load at yield

Mounting direction: 71.2 N.

Transverse direction: 60.0 N.

#### Load at break

Mounting direction: 109.0 N.

PSI: 18.6 MPa.

Transverse direction: 104.5 N.

PSI: 17.9 MPa.

#### Elongation at break

Mounting direction: 71.2 N.

Transverse direction: 60.0 N.

#### PPT resistance

Mounting direction: 60 N.

Transverse direction: 62.3 N.

#### Tongue tear

Mounting direction: 13.2 N.

Transverse direction: 22.7 N.

### Application(s)

For protection, location and identification of underground utility installations.

## LOGISTIC INFORMATION

### Packaging



#### Color sticker

Height (cm) : 15  
 Length (cm) : 13.5  
 Depth (cm) : 13.5  
 Net weight (kg) : 1.26  
 Gross weight (kg) : 1.27



### Outer package 1



#### Carton box

Height (cm) : 31  
 Length (cm) : 41  
 Depth (cm) : 28  
 Net weight (kg) : 15.24  
 Gross weight (kg) : 15.74



### Outer package 2



#### Pallet

Height (cm) : 103  
 Length (cm) : 120  
 Depth (cm) : 100  
 Net weight (kg) : 424.98  
 Gross weight (kg) : 434.98



x 324