## **Horizon D Series**

## Residential metering enclosures for NT applications

















- Designed for both single and multi-phase installations.
- · Provide safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Easy-to-use gravity catch
- · Ratchet sliding cable entry
- RotaDIN rotating / removable DIN section.
- Cord retainer for easy retention of extension cords.
- Identification with covered labelling section.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- · External frame mounting brackets.
- Meter lock-off device.
- Manufactured from 1.0 galvanised steel to Z275.
- Powdercoated Light Grey RAL7035.




## **ORDERING GUIDE**

		Inclusions		Dimensions (mm)			Panel (mm)		
Part Number	DIN space	RCCB Link#	МСВ	Height	Width	Depth	Height	Width	Depth Behind
D10*	18-pole	•	63A	600	400	300	390	385	75
D20	24-pole	•		688	485	278	480	461	75
NQ/DIN*	18-pole			600	600	270	575	560	75
Q41* <sup>†</sup>				600	400	300	550	385	75
MD061802*	18-pole			600	400	270	590	385	75

<sup>\*</sup> Sized for block construction work

<sup>†</sup>While stocks last



<sup>#</sup> RCCB Links provide RCD expansion to 3 circuits