

Product Characteristics

Part Number: CBL16WELD

CABLE WELDING FLEXIBLE 16MM 1C BLACK SHEATH

Description:



Welding Cable.

Highly flexible, double insulated cable for use with arc welding equipment rated in accordance with AS 1966.

Conductor: Plain annealed copper (AS/NZS 1125)

Insulation: Nitrile-Butadiene-PVC Copolymer (TP-90,met RoHS)

Sheath: Nitrile-Butadiene-PVC Copolymer (TP-90,met RoHS)

Voltage: 0.6/1.0KV

Attribute Name	Attribute Value
Colour outer sheath	Black
Nominal cross section conductor	16 mm ²
Number of cores	1

Classifications	
ETIM	EC000824
UNSPSC	26121604

Create Date:

Disclaimer

For use on datasheets that are created by Rexel

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.