



## Pan-Ty® PLT2I-C86 Cable Tie, Light Blue, Met Det PA6.6, 8"L, 30lb, PK100

PLT2I-C86

Panduit PLT2I-C86 Metal Detectable Cable Ties are designed to help the food, beverage and pharmaceutical industries meet product manufacturing safety standards. Featuring metal impregnated material, these metal detectable products are identifiable by metal detection equipment. Additionally, the distinct blue color facilitates quick visual detection. Intermediate cross section, 8.0" (203mm) length. Made of metal detectable Nylon 6.6, are light blue in color, and come in packages of 100.

 **Discontinued - Limited Stock**

### Suggested Replacement Parts: PLT2I-C96A

Note: It is the buyer's responsibility to determine if the suggested replacement part is suitable for your application and intended use.

## Specifications

Material Description	Nylon 6.6 ( )
Product Type	Premium Cable Tie
Color	Light Blue
Environment	Indoor
Material	Nylon 6.6
Material Properties	Metal-Impregnated
Overall Length (In.)	8
Overall Length (mm)	203
Body Width (In.)	0.135
Body Width (mm)	3.4
Body Thickness (In.)	0.047
Body Thickness (mm)	1.2
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.13
Minimum Bundle Diameter (mm)	3.3
Minimum Loop Tensile Strength (N)	133
Minimum Loop Tensile Strength (lb)	30
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185

**Specifications (continued)**

Minimum Operating Temperature (°C)	-40
Minimum Operating Temperature (°F)	-40
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS Compliant
For Use With	GTS-E, GS2B-E, STS2
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

**Packaging Detail**

UPC	07498302997
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3207