



## Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	White RAL 9003
Outlet standard	Australian/New Zealand

## Complementary

Plug, socket category	Low voltage
Device mounting	Surface
Mounting mode	External mounting
[In] rated current	16 A
[Ue] rated operational voltage	500 V AC @ 50 Hz EN 60309-2
Poles description	3P + E
Voltage colour	Black
Duration	7 h
Material	PC + PET for the cover
Contacts material	Brass for the screws
Connections - terminals	Screw terminals 1.5...6 mm <sup>2</sup> cable stiffness rigid or stranded
Tightening torque	0.8 N.m
Socket number	1
Socket-outlet type	M
Outlet standard	Industrial
Product weight	0.575 kg
Depth	102 mm
Width	101 mm
Height	107 mm
Targeted country	Australia

## Environment

ambient air temperature for operation	-25...75 °C
standards	AS/NZS 3112

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1650 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations