

KBC10DCB20

Canalis - tap-off unit - 10 A - phase selection -
without protection - L+N+PE



Main

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBA KBB KDP
Device application	Lighting
Range compatibility	Canalis KBA Canalis KBB Canalis KDP

Complementary

[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	10 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Busbar trunking polarity	L1 + N + PE L2 + L1 + L3 + PE L2 + N2 + L3 + PE
Tap-off unit polarity	L1+L2 L1+L3 L1+N L2+L3 L2+N L2+N2 L3+N L3+N3
Tap-off unit connector type	With phase selection
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	1 m
Depth	62 mm
Height	60 mm
Colour	RAL 9001 : cream
Product weight	65 g
Quantity per set	Set of 10

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.