



Main

| | |
|---------------------------|---|
| Range | Canalis |
| Product or component type | Tap-off unit |
| Device short name | KBC |
| Product compatibility | KBA KBB KDP |
| Device application | Lighting |
| Range compatibility | Canalis KBA Canalis KBB Canalis KDP |

Complementary

| | |
|--------------------------------|--------------------------------------|
| [Ue] rated operational voltage | 230...240 V |
| [Ui] rated insulation voltage | 690 V |
| [Ie] rated operational current | 16 A at 35 °C |
| Network frequency | 50/60 Hz |
| Protection type | Without protection |
| Busbar trunking polarity | L1 + N + PE L2 + L1 + L3 + N + PE |
| Tap-off unit polarity | L1+N L2+N L3+N |
| Tap-off unit connector type | With phase selection |
| Tap-off lock colour | Blue |
| Standards | EN/IEC 60439-2 EN/IEC 61439-6 |
| Width | 168 mm |
| Depth | 33 mm |
| Height | 53 mm |
| Colour | RAL 9001 : cream |
| Product weight | 90 g |
| Quantity per set | Set of 10 |

Environment

| | |
|-------------------------|---------------------------------|
| IP degree of protection | IP55 conforming to EN/IEC 60529 |
|-------------------------|---------------------------------|

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1010 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |