



Main

Range of product	Canalis
Range compatibility	Canalis KS
Product or component type	Tap-off unit
Product compatibility	Canalis KS busbar trunking with plug-in outlets
[Ie] rated operational current	20 A at 35 °C
Fuse type	Fuse isolator : for BS88 fuse, size A1 - conforming to BS standard
Provided equipment	Fuse to be ordered separately
Mounting mode	Plug-in with fixed polarity
Tap-off unit polarity	3L+N+PE
Colour	White RAL 9001

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	690 V depending on protective device
Network frequency	50/60 Hz
Electrical connection	Cable clamp terminal - ISO32 - cable : 6 mm² flexible Cable clamp terminal - ISO32 - cable : 10 mm² rigid
Door opening side	Front
Tap-off unit disconnection mode	By drawing out
Standards	IEC 61439-1 IEC 61439-6
Width	135 mm
Depth	103 mm
Height	165 mm
Product weight	0.6 kg

Environment

earthing system	TT IT TN-S
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1012 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations