## Catalogue No: **ISOSW110PGDB**

## SURFACE SWITCH 2P 10A 250V AC GREY 63mm BASE

ns)

Plugs, Sockets and Switches > Plugs and Sockets > Plugs and Sockets > ISO Plugs and Sockets > ISO Switches > Surface Switches (Including Back Boxes)





## Surface Switch 2 Pole 10A Grey Deep Base

- Large range covering 10 to 50A in 3, 4 and 5 pin configurations
- Components available: Switched Socket outlets, Switches, Socket Outlets, Plugs, Extension Sockets, Appliance Inlets, RCD Protected Outlets, Back Boxes and large range of accessories
- High ingress protection of IP66 across the range
- User friendly design with extruded ribbed grips, large switch handle and large socket latches for easy operation with or without gloves
- Suitable for most industrial and commercial applications
- Designed and tested to AS/NZS 3112 and AS/NZS 3123

Representative Photo Only
(actual product may vary based on configuration selection

SPECIFICATIONS	
Product Series	ISO
Component Type Plugs And Sockets	Surface Switch
Un, Nominal Operational Voltage, AC	250 V AC
In, Rated Current	10 A
le, Rated Operational Current, AC-23a, 250V	10 A@250V
IP Rating	IP66
Material, Body / Housing	PC (Polycarbonate) material
Colour, Body / Housing	Grey colour
Chemical Resistant Body / Housing	No body
Wire / Conductor Size (Min)	1.5 mm <sup>2</sup> min
Wire / Conductor Size (Max)	6 mm <sup>2</sup>
Switching Poles	2P qty poles
Depth	63 mm
Standards Compliance	AS/NZS 3112:2004 AS/NZS 3123:2005

REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	ISOSW110xxx, ISOSW115xxx & ISOSW120xxx_Supplier Declaration of Conformity (SDoC)
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

