Catalogue No: ISOSW132PGLB

SWITCH 2P 32A 250V AC GREY LESS BACK BOX

Plugs, Sockets and Switches > Plugs and Sockets > Plugs and Sockets > ISO Switches > Surface Switches (Less Back Box)





Representative Photo Only (actual product may vary based on configuration selections)

Surface Switch 2 Pole 32A Grey No Back Box

- Large range covering 10 to 50A in 3, 4 and 5 pin configurations
- Components available: Switched Socket outlets, Switches, Socket Outlets, Plugs, Extension Sockets, Appliance Inlets, RCD Protected Outlets, Back Boxes and large range of accessories
- High ingress protection of IP66 across the range
- User friendly design with extruded ribbed grips, large switch handle and large socket latches for easy operation with or without gloves
- Suitable for most industrial and commercial applications
- Designed and tested to AS/NZS 3112 and AS/NZS 3123

Product Series ISO Component Type Plugs And Sockets Surface Switch Un, Nominal Operational Voltage, AC 250 V AC In, Rated Current 32 A Ie, Rated Operational Current, AC-23a, 250V 32 A@250V IP Rating IP66 Material, Body / Housing PC (Polycarbonate) material Colour, Body / Housing Grey colour Chemical Resistant Body / Housing No body Wire / Conductor Size (Min) 4 mm² min Wire / Conductor Size (Max) 16 mm² Switching Poles 2P qty poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEX Certificate - Supplier Declaration of Conformity: - Installation Guide: - Liser Manual:	SPECIFICATIONS	
Un, Nominal Operational Voltage, AC In, Rated Current Ie, Rated Operational Current, AC-23a, 250V IP Rating IP66 Material, Body / Housing Colour, Body / Housing Crey colour Chemical Resistant Body / Housing Wire / Conductor Size (Min) Wire / Conductor Size (Max) Switching Poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide: - 250 V AC 250 V AC 161 182 184 184 185 186 186 187 187 188 188 188 188	Product Series	ISO
In, Rated Current Ie, Rated Operational Current, AC-23a, 250V IP Rating IP66 Material, Body / Housing Colour, Body / Housing Chemical Resistant Body / Housing Wire / Conductor Size (Min) Wire / Conductor Size (Max) Switching Poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide:	Component Type Plugs And Sockets	Surface Switch
le, Rated Operational Current, AC-23a, 250V IP Rating IP66 Material, Body / Housing Colour, Body / Housing Chemical Resistant Body / Housing No body Wire / Conductor Size (Min) Wire / Conductor Size (Max) Switching Poles Standards Compliance REFERENCES IECEx Certificate - Supplier Declaration of Conformity: Installation Guide: - Colour (Polycarbonate) material Rec (Polycarbonate) material Are (Polycarbona	Un, Nominal Operational Voltage, AC	250 V AC
IP Rating Material, Body / Housing Colour, Body / Housing Grey colour Chemical Resistant Body / Housing Wire / Conductor Size (Min) Wire / Conductor Size (Max) Switching Poles Standards Compliance REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide: - Colour, Body / Housing PC (Polycarbonate) material PC (Polycarbonate) material Area of Service colour Area of Ser		
Material, Body / Housing PC (Polycarbonate) material Colour, Body / Housing Grey colour Chemical Resistant Body / Housing No body Wire / Conductor Size (Min) 4 mm² min Wire / Conductor Size (Max) 16 mm² Switching Poles 2P qty poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3112:2005 REFERENCES IECEx Certificate - Supplier Declaration of Conformity: - Installation Guide: -	le, Rated Operational Current, AC-23a, 250V	32 A@250V
Colour, Body / Housing Grey colour Chemical Resistant Body / Housing No body Wire / Conductor Size (Min) 4 mm² min Wire / Conductor Size (Max) 16 mm² Switching Poles 2P qty poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate - Supplier Declaration of Conformity: Installation Guide: -	IP Rating	IP66
Chemical Resistant Body / Housing Wire / Conductor Size (Min) Wire / Conductor Size (Max) 16 mm² Switching Poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide: -		<u> </u>
Wire / Conductor Size (Min) Wire / Conductor Size (Max) Switching Poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide: - - - - - - - - - -		Grey colour
Wire / Conductor Size (Max) Switching Poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide: -	Chemical Resistant Body / Housing	No body
Switching Poles Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate Supplier Declaration of Conformity: Installation Guide: -	Wire / Conductor Size (Min)	4 mm² min
Standards Compliance AS/NZS 3112:2004 AS/NZS 3123:2005 REFERENCES IECEx Certificate - Supplier Declaration of Conformity: - Installation Guide: -	Wire / Conductor Size (Max)	16 mm²
AS/NZS 3123:2005 REFERENCES IECEx Certificate - Supplier Declaration of Conformity: - Installation Guide: -	Switching Poles	2P qty poles
IECEx Certificate - Supplier Declaration of Conformity: - Installation Guide: -	Standards Compliance	
Supplier Declaration of Conformity: Installation Guide: -	REFERENCES	
Conformity: Installation Guide: -	IECEx Certificate -	
liser Manual:	Installation Guide: -	
Oser Mariadi.	User Manual: -	
Manufacturer Datasheet: -	Manufacturer Datasheet: -	
Manufacturer Catalogue _		

