

PLEXO³

PRODUCT INFORMATION



Self-extinguishing: resistance to incandescent wire 650°C
 AS/NZS 3439.3
 IP65 - IK09
 Class II insulated enclosure
 Door and enclosure fully reversible
 Removable chassis and faceplates from 2-row versions up
 2 position rail for modular products and moulded cases
 Spacing between rails 150 mm
 Lockable door handle, sealable cover and faceplate
 Shock-resistant polystyrene material
 Box colour light grey L750A, cover colour dark grey R746A
 Supplied with IP2X Earth and Neutral terminal blocks
 Spare blanking plate included as a standard for 12-24-36 modules

Pack	Cat.Nos	Enclosures 4 to 8 module	
		Number of rows	Number of modules
6	601974	1	4
6	601976	1	6
6	601978	1	8

Pack	Cat.Nos	Enclosures 12 modules per row	
		Number of rows	No. of 5 module blanking plates
1	601981	1	1
1	601982	2	2
1	601983	3	2

Pack	Cat.Nos	Accessories
1	01966	Key lock N° 850
1	01969	Fixing lugs Set of 4 wall mounting lugs
20	01961	Blanking plates 5, separable into modules or 1/2 module, Grey R746A
1	01955	Direct piercing end caps Pack consisting of 2 Ø32mm ISO end caps, 5 Ø25mm ISO end caps and 10 Ø20mm ISO end caps



Scan the QR code for data sheet

