

33170
carriage auxiliary switch NO/NC 6 A - 240 V - for
Masterpact NT/NW NS630b..1600



Main

Device short name	Carriage switch
Product or component type	Auxiliary contact
Device application	Control
Range compatibility	Masterpact - Masterpact NW Masterpact - Masterpact NT Compact - Compact NS630b...1600
Offer type	C4
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Connected position Disconnected position Test position
Mounting mode	Drawout
[Ie] rated operational current	DC-12 : 0.3 A DC 250 V AC-12 : 8 A AC 50/60 Hz 380 V AC-12 : 6 A AC 50/60 Hz 690 V AC-12 : 8 A AC 50/60 Hz 240 V AC-12 : 8 A AC 50/60 Hz 480 V DC-12 : 0.8 A DC 125 V DC-12 : 2.5 A DC 24/48 V
Minimum load	100 mA at 24 V
Accessory / separate part category	Spare part Compact NS630b...1600 Spare part Masterpact NT Spare part Masterpact NW

Environment

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.