

Data Cables – Overall Screened

Application:	Internal and external inter-connections of electronic apparatus such as computers, intercoms, signalling and alarm systems.
Conductor:	Tinned Annealed Copper Wire
Insulation:	Multi-Core – PVC V-75, Multi-Pair – Polypropylene
Paired Cores:	Twisted
Screen:	Aluminium Tape Screen, Polyester Mylar Tape lapping and Tinned Copper Drain Wire.
Sheath:	PVC 4V-75
Voltage:	240V Radial Thickness Sheath –
Standards:	AS1125 (Conductor), AS/NZS 3808 (PVC)
Greenstar:	Approved
	MUST NOT BE CONNECTED TO MAINS

ELECTRA PART NUMBER	CORES	SIZE	O.D.
EAS7204	4	0.22	4.8
EAS7206	6	0.22	5.7
EAS7208	8	0.22	6.3
EAS7210	10	0.22	7.0
EAS7212	12	0.22	7.4

*O.D. ± 10% = mm *Size = mm²

ELECTRA PART NUMBER	PAIRS	SIZE	O.D.
EAS7201P	1	0.22	4.2
EAS7201PHV*	1	0.22	4.8
EAS7202P	2	0.22	5.7
EAS7203P	3	0.22	5.9
EAS7204P	4	0.22	6.4
EAS7206P	6	0.22	7.5
EAS7208P	8	0.22	8.6
EAS7210P	10	0.22	9.7
EAS7212P	12	0.22	10.3

*(PHV) 0.6/1kV Insulation Radial *O.D. ± 10% = mm *Size = mm

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628