

LIGHTING CONTROLS

MOTION DETECTOR 180° EXTERNAL PIR



R180-01	White
R180-04	Black
Depth (mm):	130
Width (mm):	75
Height (mm):	85
Box Qty:	30
Weight (Kg):	0.36
IP:	44
Guarantee:	5
Detection Range at 2.5(M):	12
Time delay off:	10 s to 10m
Lux Setting (Lx):	2 to 2000
Contact Load (W):	Fluorescent -300 Incandescent - 1200

High energy costs and the need to lower the CO2 emissions our buildings contribute towards global warming make lighting control one of the most important factors to consider in our lighting installations. These attractive and functional detectors help to achieve these goals by switching our lighting off automatically when it is not required and switching it on when it is needed. Passive Infrared technology combined with Photo-electric control ensures that the minimum amount of energy is used and thereby reduces the buildings Carbon Footprint. Often used outdoors, but also with indoor applications these detectors are used to control lighting in domestic, commercial, retail and service areas. Areas of application include:

- Gardens
 - Parking areas
 - Driveways
- Decking areas
 - Loading bays
 - Corridors
- Patios
 - Stairways
 - Corner mounting in larger rooms
- Paths & walkways
 - Passages

FEATURES	BENEFITS
<ul style="list-style-type: none"> • Polycarbonate body 	<ul style="list-style-type: none"> • Robust • Vandal resistant
<ul style="list-style-type: none"> • Available in black or white 	<ul style="list-style-type: none"> • Choice of colours to match the area installed within
<ul style="list-style-type: none"> • 180° detection • 12m sensing distance 	<ul style="list-style-type: none"> • Effective detection ensures lighting is switched on when required
<ul style="list-style-type: none"> • 10 sec – 10 min adjustable ON time delay • 0 – 30 adjustable lux level 	<ul style="list-style-type: none"> • Quick setup with 10 second walk test • Guarantee energy saving by switching off after delay • Saves on energy costs by inhibiting the lighting when it is light enough
<ul style="list-style-type: none"> • Manual override • Automatic reset 	<ul style="list-style-type: none"> • Allows manual switch on for up to 8 hours before resetting to continue energy saving
<ul style="list-style-type: none"> • 1200W Incandescent, 300W fluorescent load 	<ul style="list-style-type: none"> • High contact rating for switching multiple lights in an area
<ul style="list-style-type: none"> • 5 year guarantee 	<ul style="list-style-type: none"> • A quality energy efficient long life product • Peace of mind

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE