

LIGHTING CONTROLS

INTERNAL PASSIVE INFRA-RED DETECTOR



RR360-01	White
Diameter(mm):	75
Depth(mm):	60
Cut Out (mm):	62
Weight (Kg):	0.14
IP:	20
Guarantee:	5
Detection Range at 2.8m(M):	8
Time delay off:	10 s to 16m
Max Watt (W):	Fluorescent -500 Resistive- 1000

This high quality great looking recessed sensor has a slim profile and will contribute to the energy savings required to meet the carbon reduction targets of our buildings. Combining passive infra-red and photocell technology, it ensures the lighting comes on only when natural light alone is not enough, although the lux level setting may be set to ensure lighting and fans are activated in toilet areas. It is suitable for switching resistive or fluorescent type loads in all building types and finds applications for switching lighting in:

- Commercial offices
 - "Back of house" areas
 - Storage rooms
- Stairways
 - Corridors
 - Workshops
- Sheds
 - Toilets
 - Garages
- Kitchens
 - Basements
 - Apartment communal areas

FEATURES	BENEFITS
<ul style="list-style-type: none"> • Injection moulded ABS body 	<ul style="list-style-type: none"> • Strong, durable and impact resistant • Less susceptible to damage
<ul style="list-style-type: none"> • Clear terminal cover • Integral cable clamp • Large mains terminals for 2 x 1.5mm² conductors 	<ul style="list-style-type: none"> • Terminations are safe and visible • Cables are clamped for safety • Enables loop- in, loop-out for supply to other sensors • Provides for 2 switch wires for switching additional fittings
<ul style="list-style-type: none"> • Good quality spring clips 	<ul style="list-style-type: none"> • Ensures the sensor is pulled flush to the surface
<ul style="list-style-type: none"> • Passive infra-red 	<ul style="list-style-type: none"> • Ensures the light is switched on when sensor detects movement of heat • Saves energy by ensuring lighting is switched off when the area is vacated • Less likely to false trigger compared to microwave which switches on any movement
<ul style="list-style-type: none"> • Photocell 	<ul style="list-style-type: none"> • Even more energy saving by only switching the lighting on if the ambient level is not sufficient
<ul style="list-style-type: none"> • Off delay timer 10 sec - 16mins 	<ul style="list-style-type: none"> • 10 second setting enables walk test to ensure the sensor is operating correctly • Short time delay used for tungsten lighting • Longer time delay for fluorescent, PL, and 2D lighting
<ul style="list-style-type: none"> • 8m diameter sensing when mounted at 2.8m high 	<ul style="list-style-type: none"> • Provides area sensing and can be linked to other sensors for larger areas such as long corridors of offices
<ul style="list-style-type: none"> • 5 year guarantee 	<ul style="list-style-type: none"> • A quality energy efficient long life product

PLEASE NOTE – INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE