

## Flexible Cord Cable – Figure 8

**250/250V PVC V90 Copper or Tinned copper conductor Flexible Cable.**

**Application:** Suitable to use for wiring of audio, electronic and allied equipment

**Conductor:** Plain annealed copper wire

**Insulation:** PVC 90°C (AS3808)

**Sheath:** PVC 90°C

**Voltage:** 250/250V

**Standards:** AS3191

**Pack Length:** 100m, 500m

### Typical Features:

Electra Cables Part No.	Nominal area mm <sup>2</sup>	Stranding No/mm No. of cores	Nominal O.D. mm	Nominal insulation Thickness mm	Amp Rating	Electrical Resistance @ 20°C Ω/Km
F2875	0.75	24/0.20x2	5.9x2.7	0.8	7.5	26
F2810	1.0	32/0.20x2	6.2x2.9	0.8	10	19.5
F2815	1.5	30/0.25x2	6.8x3.2	0.8	15	13.3
F2825	2.5	50/0.25x2	8.2x3.8	0.9	20	8.0

**(FLAT) Insulation:** PVC 90°C (AS3808)

**Sheath:** PVC 90°C

Electra Cables Part No.	Nominal area mm <sup>2</sup>	Stranding No/mm No. of cores	Nominal O.D. mm	Nominal insulation Thickness mm	Nominal sheath Thickness mm	Amp Rating	Electrical Resistance @ 20°C Ω/Km
FF2075	0.75	24/0.20x2	5.9x2.7	0.6	0.5	7.5	26

**Conductor:** Tinned Copper

**Sheath:** Clear PVC 90°C

Electra Cables Part No.	Nominal area mm <sup>2</sup>	No. of cores	Stranding No/mm	Nominal O.D. mm	Insulation Thickness mm	Amp Rating	Electrical Resistance @ 20°C Ω/Km
F2875Clear	0.75	2	24/0.20	5.9x2.7	0.8	7.5	26
F2810Clear	1.0	2	32/0.20	6.2x2.9	0.8	10	19.5
F2815Clear	1.5	2	30/0.25	6.8x3.2	0.8	15	13.3
F2825Clear	2.5	2	50/0.25	8.2x3.8	0.9	20	7.4

### Colour Codes:

Cable codes	Sheath Colours with trace
F2875	Red, Black, White, Grey, Blue, Brown
F2810	Red, Black, White, Grey, Blue, Brown
F2815	Black, White
F2825	Red
FF2075	Blue/Brown cores with Black or White sheath