



# Technical Data Bulletin



### Construction:

Body:	Fabricated 'Zincseal' sheet.
Front Cover:	Folded "Zincseal" sheet, powder coated white.
Top Cover:	Polycarbonate white plastic.
Console:	Polycarbonate charcoal plastic.
Side Vents:	Polycarbonate white plastic.
Grill:	Formed MS wire, powder coated black.
Motor/Fan:	Fractional horsepower, shaded pole, motor with tangential "barrel" fan.
Element:	Nickel Chromium, helical wound wire, supported on formers with a metal surround,
	incorporating fibreglass supporting cordage.
Thermostat:	Rotary thermostat turns the heater to off when room temperature is reached.
Thermal Protection:	Primary - Self-resetting, mechanical cutout.
	Secondary - Non-resetting thermal fuse.
Timer:	Fully programmable, 24 hour, with rotating front face - optional.
On/Off Switch:	Rocker type with inbuilt indicator light.
Wiring:	150 Degree, silicon wire with (120c) insulating "Boots" in all high temperature areas.
Knobs:	Polycarbonate.
Fasteners:	Zinc passivated.

### **Dimensions:**

Width:	
Height:	
Depth:	

## Features:

- Available in 2.4, 3.5, 4.5kw Modern, curved design Full electrical approval Top cover for full protection of all controls. Simple surface mounting

530 mm 640 mm 120 mm

24hr Fully programmable timer.



9/3 Lancaster St Ingleburn NSW 2565 Ph: 02 9618 3842 Fax: 02 9829 2603

Distributed by:				
NSW:	D.R. Distribution	~ p: 02 9618 3842		
QLD:	D.R. Distribution	~ p: 02 9618 3842		
SA:	D.R. Distribution	~ p: 02 9618 3842		
WA:	D.R. Distribution	~ p: 02 9618 3842		
VIC:	D.R. Distribution	~ p: 02 9618 3842		
TAS	Electrical Agencies	~ p: 02 9618 3842		





# Technical Data Bulletin



## Models Available:

KW	PRODUCT CODE	
White - Thermostat Only		
2.4	OE24W	
3.5	OE35W	
4.5	OE45W	
White - c/w Thermostat & 24hr Timer		
2.4	OE24TW	
3.5	OE35TW	
4.5	OE45TW	

## Method of Operation

Air is drawn in through the rear of the side mounted vent panels & past the thermostat sensing bulb by a motor coupled to a tangential 'barrel' fan. The air continues through the element and exits the heater via the bottom front grill creating a continuous cycle of warm air into the room. The air temperature is thermostatically controlled, allowing the heater to turn off and on to maintain the desired room temperature. The optional 24hr fully programmable timer can be set, via its tabs, to achieve any number of on/off settings, in minimum 15 minute intervals, through any 24hr period.



D.R. Distribution Pty Ltd 9/3 Lancaster St Ingleburn NSW 2565 Ph: 02 9618 3842 Fax: 02 9829 2603 E: tammy@drdistribution.com.au

Distributed by:		
NSW:	D.R. Distribution	~ p: 02 9618 3842
QLD:	D.R. Distribution	~ p: 02 9618 3842
SA:	D.R. Distribution	~ p: 02 9618 3842
WA:	D.R. Distribution	~ p: 02 9618 3842
VIC:	D. R. Distribution	~ p: 02 9618 3842
TAS:	Electrical Agencies	~ p: 02 9618 3842