

Balaclava - IIIA Nomex

For hazards like arc flash, flash fire, pool fire, and molten metal splash, DuPont created Nomex® III A – a blend of 93% Nomex® with 5% Kevlar® and 2% antistatic fiber that expands to form a stable and inert barrier between fire and skin.

KEY FEATURES & BENEFITS:

- NOMEX® IIIA double layer flame retardant balaclava
- Calculated to Cat 2A (8cal/cm²)
- Extra Arc Flash face protection
- Double layer front
- Single layer rear



Part No.	S	M	L	XL	Description
0024B-NOMEX	One size fits most				Balaclava IIIA Nomex®

CAT RATING GUIDE



Minimum 4 cal/cm²
Lightweight all day workwear.



Minimum 8cal/cm²
NFPA 70E
Heavy duty all day workwear.



Minimum 25cal/cm²
NFPA 70E
Over garments to bridge the gap between Cat2 and Cat4.



40cal/cm² NFPA 70E
Highest possible protection available.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

AU T: 133 122 | F: 1300 303 310 | E: sales@cabac.com.au | W: cabac.com.au

NZ T: 0800 77 69 69 | F: 0800 88 69 69 | E: sales@cabac.co.nz | W: cabac.co.nz