



Kyoritsu 2200 ultra slim clamp meter

Features at a glance

- Ultra slim and lightweight design
- 1000A AC clamp meter - AC40/400/1000A auto range
- 33mm tear drop jaw makes it easy to use in tight places
- DMM function ACV, DCV, Ω , continuity buzzer
- Fuseless electronic protection on resistance and continuity function up to 600V

Specifications

AC A	40.00/400.0/1000A (Auto-ranging) $\pm 1.4\%rdg \pm 6dgt$ (50/60Hz) $\pm 1.6\%rdg \pm 6dgt$ (45~65Hz)
AC V	4.000/40.00/400.0/600V (Auto-ranging) $\pm 1.8\%rdg \pm 7dgt$ (45~65Hz) $\pm 2.3\%rdg \pm 8dgt$ (65~500Hz)
DC V	400.0mV/4.000/40.00/400.0/600V (Auto-ranging) $\pm 1.0\%rdg \pm 3dgt$
Ω	400.0 Ω /4.000/40.00/400.0k Ω /4.000/40.00M Ω (Auto-ranging) $\pm 2.0\%rdg \pm 4dgt$ (0~400k Ω) $\pm 4.0\%rdg \pm 4dgt$ (4M Ω) $\pm 8.0\%rdg \pm 4dgt$ (40M Ω)
Conductor size	$\varnothing 33mm$ max.
Withstand voltage	5320V AC for 5 seconds (AC A) 3540V AC for 5 seconds (AC/DC V)
Applicable standards	IEC 61010-1 CAT.III 600V (AC A), CAT.III 300V / CAT.II 600V (AC/DC V) IEC 61010-031, IEC 61010-2-032, IEC 61326 (EMC)
Power source	R03/LR03 (AAA) (1.5V) \times 2
Dimensions	190(L) \times 68(W) \times 20(D)mm
Weight	120g (including batteries)
Accessories	7107A (Test leads), 9160 (Carrying case)