

Quick Overview

Raychem WCSM Heavy Wall Tubing Adhesive Lined



Features

Raychem WCSM Heavy Wall Tubing Adhesive Lined

- Heat shrinkable heavy wall adhesive lined insulating tubing
- Low voltage joints (direct burial)
- Submersed joints
- Electrical insulation & jacketing
- Corrosion protection
- Mechanical protection

Details

Part No.	RAYWCSM48/12
Brand	Raychem
Unit Of Measure	Each
Compendium Page #	361

Additional Information

Part No.	Application Range (Diameter)	Diameter		Wall Thickness	
		As Supplied Minimum (mm)	After Free Recovery Maximum (mm)	As Supplied Minimum (mm)	After Free Recovery Minimum (mm)
RAYWCSM16/4	4.5 - 14	16	4	0.9	2.4
RAYWCSM24/6	6.5 - 22	24	6	1.0	2.7
RAYWCSM34/8	9.0 - 31	33	8	1.3	4.0
RAYWCSM48/12	13.0 - 44	48	12	1.5	4.5
RAYWCSM56/16	17.5 - 50	56	16	1.5	4.4
RAYWCSM70/20	22.0 - 63	70	20	1.4	4.4
RAYWCSM90/25	27.0 - 81	90	25	1.3	4.3
RAYWCSM110/30	33.0 - 100	110	30	1.2	4.3
RAYWCSM130/35	38.0 - 118	130	35	1.2	4.3
RAYWCSM180/50	55.0 - 162	180	50	1.0	4.3

Note: • Standard lengths of 1200 mm.
• Maximum longitudinal change after free recovery: - 15% up to 43/12
- 10% above 43/12