

Catalogue No: **1734-ADN**
POINT I/O 24V DC DNET ADAPTER

Automation Systems > Distributed I/O and Signal Converters > Fieldbus I/O Systems > Allen-Bradley Point I/O™ > POINT I/O™ Communication Adapters



Point I/O DeviceNet 24V DC Adapter



- Built-in power supply powers the I/O modules through the backplane
- Up to 63 I/O modules per assembly, for up to 504 points on a single network node
- Provide the interface between the POINT I/O™ modules and backplane, and the desired network
- Snap directly onto the DIN rail

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS	
Product Series	Point I/O (Bul. 1734)
Component Type Fieldbus I/O	Communications Module
Communications Ports (On Board)	DeviceNet Peer to Peer/Slave
Communication Port Speed (Min.)	125 kbit/s
Communication Port Speed (Max.)	500 kbit/s
Communications Protocols	DeviceNet
Power Supply	24V DC
Operating Temperature, Max	55 °C max
Operating Temperature, Min	-20 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-