



Representative Photo Only  
(actual product may vary based on configuration selections)

**ControlLogix 5573 Processor 8MB**

- Offer flexible user memory options
- Communicates via EtherNet/IP™, ControlNet™, DeviceNet™, Data Highway Plus™, Remote I/O, SynchLink, and third-party process and device networks
- Includes conformal coating on products that include a "K" in the catalogue number, to help protect in harsh environments

**SPECIFICATIONS**

Product Series	ControlLogix (Bul. 1756 / 1757)
Component Type PLC & I/O	Controller
Memory, Controller	8 MB memory
Memory Card Type	SD
Memory Card, Installed	1 GB
Memory Card Option	SD Card
Communications Ports (On Board)	USB (programming only)
Communications Protocols	ControlNet DeviceNet EtherNet/IP EtherNet/OCPP Remote IO DH+ SynchLink
Maximum Digital I/O	128000
Maximum Analogue I/O	4000
Maximum Total I/O	128000
Safety Controller	No
Software, Configuration	RSLogix5000 / Studio 5000 (Logix Designer)
Weight	0.25 kg
Power Dissipation, Max	2.5 W
Operating Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing
Shock Rating	IEC 60068-2-27
Vibration Acceleration (Max.)	2 m/s <sup>2</sup>
Vibration Frequency, Operational (Max.)	500 Hz

# Catalogue No: **1756-L73**

## CONTROLLOGIX 5573 PROCESSOR 8MB

Automation Systems > Modular Programmable Controllers > Large PLC Systems > Allen-Bradley ControlLogix® > ControlLogix® and GuardLogix® Controllers > ControlLogix® L7x Controllers



Vibration Rating IEC 60068-2-6

Standards Compliance IEC 60068-2-1  
IEC 60068-2-14  
IEC 60068-2-2  
IEC 60068-2-27  
IEC 60068-2-30  
IEC 60068-2-6  
IEC 61000-4-2  
IEC 61000-4-3  
IEC 61000-6-4

Certifications CE  
KC (KCC)  
C-Tick

### REFERENCES

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue & Product Selection: -