Catalogue No: **1756-L75**

CONTROLLOGIX 5575 PROCESSOR 32MB





ControlLogix 5575 Processor 32MB

- · Offer flexible user memory options
- Communicates via EtherNet/IP™, ControlNet™, DeviceNet™, Data Highway Plus™, Remote I/O, SynchLink, and third-party process and device networks
- Includes conformal coating on products that include a "K" in the catalogue number, to help protect in harsh environments

SPECIFICATIONS		
Product Series	ControlLogix (Bul. 1756 / 1757)	
Component Type PLC & I/O	Controller	
Memory, Controller	32 MB memory	
Memory Card Type	SD	
Memory Card, Installed	1 GB	
Memory Card Option	SD Card	
Communications Ports (On Board)	USB (programming only)	
Communications Protocols	ControlNet DeviceNet EtherNet/IP EtherNet/OCPP Remote IO DH+ SynchLink	
Maximum Digital I/O	128000	
Maximum Analogue I/O	4000	
Maximum Total I/O	128000	
Safety Controller	No	
Software, Configuration	RSLogix5000 / Studio 5000 (Logix Designer)	
Weight	0.25 kg	
Power Dissipation, Max	2.5 W	
Operating Temperature, Max	60 °C max	
Operating Temperature, Min	0 °C min	
Storage Temperature, Max	85 °C max	
Storage Temperature, Min	-40 °C min	
Relative Humidity, Max	95 %RH	
Humidity Type	Non-condensing	
Shock Rating	IEC 60068-2-27	
Vibration Acceleration (Max.)	2 m/s ²	
Vibration Frequency, Operational (Max.)	500 Hz	



Catalogue No: **1756-L75**

CONTROLLOGIX 5575 PROCESSOR 32MB





Vibration Rating	IEC 60068-2-6	
Standards Compliance	IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-27 IEC 60068-2-30 IEC 60068-2-6 IEC 61000-4-2 IEC 61000-4-3 IEC 61000-6-4	
Certifications	CE KC (KCC) C-Tick	
REFERENCES		
IECEx Certificate -		
Supplier Declaration of Conformity:		
Installation Guide: -		
User Manual: -		
Manufacturer Datasheet: -		
Manufacturer Catalogue		



& Product Selection: