



HART Analog Output Modules, 8 Single-Ended Outputs Isolated



- Cover a wide electrical range
- Densities range from 8...32 points
- Isolated inputs or outputs, protected outputs, electronic fusing, or diagnostics available on some modules
- Removal and Insertion Under Power (RIUP) lets you replace modules and make cable connections while the system is in operation
- FLEX-I/O XT™ extreme environment modules are rated for -20...70 °C (-4...185 °F) and are compatible with the ControlLogix-XT™ extreme environment system. Contact NHP for further information.
- Each I/O module requires a terminal base for connection points for I/O wiring
- Wire directly from sensor to terminal base of the Flex™ I/O module and eliminate the terminal strip
- Conformally coated modules are available, please contact NHP for further details

Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Product Series	Flex I/O (Bul.1794)
Component Type Fieldbus I/O	Analogue Output Module
Number of Analogue Outputs	8 qty
Analogue Output Type(s)	HART - Current: Singled-Ended, Isolated
Analogue Output Range(s)	0 ... 20mA 4 ... 20mA
Analogue Resolution, Output	16 bit (unsigned)
Power Supply	24V DC
Module Specific Functions	Interface analog signals with any programmable controller have block transfer capability
Operating Temperature, Max	55 °C max
Operating Temperature, Min	0 °C min

**REFERENCES**

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-