

Catalogue No: **440G-MT47044**

440G-MT SWITCH 2NC-SFTY 2NO-AUX 24V DC SOLENOID GD2-STND-ACT

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley 440G GuardLocking Switches > 440G-MT



Guard Locking Switch - 440G-MT Solenoid: Solenoid Voltage: 24V AC/DC, Contacts(Safety and Aux): 2 Normally Closed, 2 Normally Open, Actuator: Standard, Conduit Entry: M20 Conduit

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Safety Switch Type	Guard Locking Switch type
Number of Safety Contacts	2 qty safety
Output Configuration, Safety	2 NC
Number of Aux Contacts	2
Output Configuration, Auxiliary	2 NO
Solenoid Voltage, AC, Nom	24 V AC
Solenoid Voltage, AC/DC, Nom	24 V AC/DC
Holding Force, Max	1600 N
Conduit Entry	M20 entry
Connection / Termination	M20
Actuator Included	Yes Y / N
Un, Nominal Operational Voltage, AC	24 V AC
Un, Nominal Operational Voltage, DC	24 V DC
Material, Body / Housing	Zinc Alloy, Die-Cast, Painted material
Operating Temperature, Max	60 °C max
Operating Temperature, Min	-25 °C min
Storage Temperature, Max	60 °C max
Storage Temperature, Min	-25 °C min
IP Rating	IP67
Height	40 mm
Depth	199 mm
Width	46.75 mm



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-