

Catalogue No: **889D-R4AC-2**

CABLE PVC YELLOW 4PIN 22AWG DC-MICRO-F-RA 2M

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Pre-Wired Cables and Connection Systems > Allen-Bradley Connection systems > DC Micro, 4-Pin > Cordsets



DC Micro (M12), Female, R-Angle, 4-Pin, PVC Cable, Yellow, Unshielded, 22 AWG, IEC Color Coded, No Connector, 2 m (6.56 ft.)



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--|--|
| Product Series | 889 Cordsets and Patchcords |
| Component Type Termination Wiring | Cordset (1 Connector, 1 Set of Flying Leads) |
| Connector A | M12 x 1, DC Micro, 4-pin |
| Gender, Connector A | Female ConnectorA |
| Orientation, Connector A | Right Angle ConnectorA |
| Connector B | Flying leads (no connector) |
| In, Rated Current | 4 A |
| Ue, Rated Operational Voltage, AC, max | 250 V AC |
| Material, Contacts | Gold-Plated Brass material |
| Bend Radius | 50 mm |
| Material, Coupling Nut | Epoxy-Coated Zinc |
| Material, cable jacket | PVC material |
| Colour, Cable Jacket | Yellow colour |
| Diameter, Cable Jacket | 5 mm |
| Number of Conductors | 4 qty |
| Wire / Conductor Size | 22 AWG (0.326 mm ²) |
| Length, Cable | 2 m |
| IP Rating | IP69K |
| Operating Temperature, Min | -20 °C min |
| Operating Temperature, Max | 105 °C max |

Catalogue No: **889D-R4AC-2**

CABLE PVC YELLOW 4PIN 22AWG DC-MICRO-F-RA 2M

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Pre-Wired Cables and Connection Systems > Allen-Bradley Connection systems > DC Micro, 4-Pin > Cordsets



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -