



GROUND S9338 - 3W


3 watt adjustable LED inground luminaire, IP67 rated

Application

Decorative residential exterior solution, ideal for gardens and decorative pathways

Design Specifications

- Die-cast aluminium body
- Stainless steel face panel & screws, clear tempered glass diffuser
- High output LED optics 24V DC driver required
- Beam angle 30°, optical adjustment between 50°~60°
- PC installation canister included, pre-wired 600 mm 2 core rubber flex
- Suitable LED drivers, PLUTO 15DV, PLUTO 40DV, PLUTO 60DV, PLUTO 100/24V, IK08, IP67 performance



Performance

- Dimmable - **NO**



Technical Specification

Product	Model No.	Input Voltage (V/DC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	S9338/3W/30WW	24	3	150	3000	70
	S9338/3W/30DL	24	3	200	6000	70

Beam Angle (°)	Diameter (mm)	Dim (mm)	Body Colour
30	130	115(H)	STAINLESS STEEL
30	130	115(H)	STAINLESS STEEL

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

S9338

Optical adjustment

