

Catalogue No: **2080-OW4I**  
**M820/M830/M850 PLUG-IN 4DO RLY**

Automation Systems > Micro Programmable Controllers and Smart Relays > Micro PLCs > Allen-Bradley® Micro820®, Micro830®, Micro850® and Micro870® Controllers > Micro800® Plug-in Modules > Micro800® Digital I/O Plug-In Modules



Representative Photo Only  
 (actual product may vary based on configuration selections)

**Micro800 Plug-In Modules, 4 Digital Outputs - 2A Relay Isolated**

- Available for additional I/O, communications, backup memory and speciality capabilities
- Snaps easily into controller without expanding the footprint
- Operates in -20 to 65 degrees celcius temperatures

**SPECIFICATIONS**

Product Series	Micro800 (Bul. 2080)
Component Type PLC & I/O	Relay Output Module
Operating Temperature, Max	65 °C max
Operating Temperature, Min	-20 °C min
Storage Temperature, Max	85 °C max
Storage Temperature, Min	-40 °C min
Relative Humidity, Max	95 %RH
Humidity Type	Non-condensing
Shock Acceleration (Max.)	25 g
Vibration Acceleration (Max.)	2 m/s <sup>2</sup>
Vibration Frequency, Operational (Max.)	500 Hz
Vibration Rating	IEC 60068-2-6

**REFERENCES**

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-