

PRODUCT DATASHEET

HQI-T 250 W/D

POWERSTAR HQI-T | Metal halide lamps with quartz technology for enclosed luminaires



AREAS OF APPLICATION

- Factories and workshops
- Sports halls and multi-purpose halls
- Industrial installations
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Output of up to 400 W
- High efficiency
- Long lifetime
- E40 screw base for simple lamp handling
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

PRODUCT FEATURES

- POWERSTAR quartz technology
- Light colors: neutral white (N), daylight (D)



TECHNICAL DATA

Electrical data

Rated wattage	250.29 W
Lamp current	3.0 A
Nominal wattage	250.29 W

Photometrical data

Rated luminous flux	19000 lm
Color temperature	5500 K
Light color	955
Light color (designation)	Daylight
Luminous flux	19000 lm
Color rendering index Ra	92

Dimensions & weight



Diameter	46.0 mm
Length	226.0 mm
Product weight	163.00 g

Additional product data

Base (standard designation)	E40
Design / version	clear
Mercury content	18.0 mg

Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	Yes

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321628640	Sleeves 1	52 mm x 52 mm x 292 mm	199.00 g	0.79 dm ³
4008321628657	Shipping carton box 12	262 mm x 211 mm x 319 mm	2548.00 g	17.63 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.