

QO120VSC10

QOvs - miniature circuit-breaker - 1P - C curve - 20A
- 10kA



Main

Device application	Distribution
Range	Square D
Product name	QOvs
Product or component type	Miniature circuit-breaker
Poles description	1P
Number of protected poles	1
[In] rated current	20 A
Network type	AC
Curve code	C
Breaking capacity	10 kA Icn conforming to EN/IEC 60898-1 - 240 V AC 50/60 Hz

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	240/415 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	7.5 kA 75 % conforming to EN/IEC 60898-1 - 240 V AC 50/60 Hz
Limitation class	3
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60898-1
Contact position indicator	Yes
Control type	Toggle
Local signalling	Fault trip ON/OFF indication
Mounting mode	Plug-on
9 mm pitches	2
Height	81 mm
Width	18.7 mm
Depth	86.3 mm
Product weight	104 g
Colour	Black
Mechanical durability	20000 cycles
Electrical durability	4000 cycles
Connections - terminals	Tunnel type terminals, bottom rigid wire(s) 1...25 mm ² max Tunnel type terminals, bottom flexible wire(s) 1...25 mm ² max Plug-in connector, top
Wire stripping length	13 mm bottom
Tightening torque	2 N.m bottom

Environment

standards	EN/IEC 60898-1
product certifications	IEC
IP degree of protection	IP20 conforming to IEC 60529
pollution degree	3
tropicalisation	2 conforming to IEC 60068-1
relative humidity	95 % 55 °C
ambient air temperature for operation	-5...60 °C
ambient air temperature for storage	-40...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.
