



Main

Range of product	Sepam series 20 Sepam series 40 Sepam series 80 Sepam series 48 Sepam series 80 NPP Sepam series 60
Device short name	ACE959

Complementary

Communication port protocol	Modbus RTU network: E-LAN interface: RS485 - 4-wire Modbus RTU network: E-LAN interface: RS485 - 4-wire Modbus RTU network: S-LAN interface: RS485 - 4-wire
Local signalling	LED for link activity on front face
[Us] rated supply voltage	12 V DC tolerance: +/- 10 % 24 V DC tolerance: +/- 10 %
Supply current	<= 16 mA : receiving mode <= 40 mA : maximum in sending mode
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Height	88 mm
Width	144 mm
Depth	30 mm
Product weight	0.2 kg
Mechanical robustness	Earthquakes in operation (level: 2) : 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2) : 1 Gn (vertical axes) conforming to IEC 60255-21-3 Earthquakes in operation (level: 2) : 2 Gn (horizontal axes) conforming to IEC 60255-21-3 Jolts de-energized (level: 2) : 20 Gn/16 ms conforming to IEC 60255-21-2 Shocks de-energized (level: 2) : 27 Gn/11 ms conforming to IEC 60255-21-2 Shocks in operation (level: 2) : 10 Gn/11 ms conforming to IEC 60255-21-2 Vibrations de-energized (level: 2) : 2 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: 2) : 1 Gn, 10 Hz...150 Hz conforming to IEC 60255-21-1 Vibrations in operation (level: Fc) : 2 Hz...13.2 Hz, a = +/- 1 mm conforming to IEC 60068-2-6
Cable distance between devices	10 Devices <= 180 m cable length at 12 V DC 10 Devices <= 750 m cable length at 24 V DC 20 Devices <= 160 m cable length at 12 V DC 20 Devices <= 450 m cable length at 24 V DC 25 Devices <= 125 m cable length at 12 V DC 25 Devices <= 375 m cable length at 24 V DC 5 Devices <= 1000 m cable length at 24 V DC 5 Devices <= 320 m cable length at 12 V DC
Auxiliary connection terminal	Earthing terminal : screw-type connector cable 2.5...50 mm ² <= 0.2 m Earthing terminal : screw-type connector tinned copper braid 6...100 mm ²
Tightening torque	Earthing terminal : 2.2 N.m

Environment

electromagnetic compatibility	1 MHz damped oscillating wave immunity tests-conducted disturbances (2.5 kV CM, 1 kV DM) conforming to IEC 60255-22-1
-------------------------------	--

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

1 MHz damped oscillating wave immunity tests-conducted disturbances (2.5 kV CM, 2.5 kV DM) conforming to ANSI C37.90.1
 100 kHz damped oscillating wave immunity tests-conducted disturbances (2.5 kV CM, 1 kV DM) conforming to IEC 61000-4-12
 Conducted disturbance emission tests conforming to IEC 60255-25
 Disturbing field emission tests conforming to IEC 60255-25
 Electrostatic discharge immunity tests-radiated disturbances (8 kV air, 4 kV contact) conforming to ANSI C37.90.3
 Electrostatic discharge immunity tests-radiated disturbances (8 kV air, 6 kV contact) conforming to IEC 60255-22-2
 Fast transient bursts immunity tests-conducted disturbances (4kV, 2.5 kHz) conforming to ANSI C37.90.1
 Immunity to radiated fields immunity tests-radiated disturbances (10 V/m, 80 MHz...1 GHz) conforming to IEC 60255-22-3
 Immunity to radiated fields immunity tests-radiated disturbances (35 V/m, 25 MHz...1 GHz) conforming to ANSI C37.90.2
 Voltage interruptions immunity tests-conducted disturbances (100 % during 100 ms) conforming to IEC 60255-11
 Fast transient bursts immunity tests-conducted disturbances : IV (4kV, 2.5 kHz) conforming to IEC 61000-4-4
 Immunity to radiated fields immunity tests-radiated disturbances : III (10 V/m, 80 MHz...2 GHz) conforming to IEC 61000-4-3
 Disturbing field emission tests : A conforming to EN 55022
 Fast transient bursts immunity tests-conducted disturbances : A and B (4kV, 2.5 kHz/2 kV, 5 kHz) conforming to IEC 60255-22-4
 Fast transient bursts immunity tests-conducted disturbances : A and B (4kV, 2.5 kHz/2 kV, 5 kHz) conforming to IEC 60255-22-4
 Immunity to conducted RF disturbances immunity tests-conducted disturbances : III (10 V) conforming to IEC 60255-22-6
 Conducted disturbance emission tests : A conforming to EN 55022
 Immunity to magnetic fields at network frequency immunity tests-radiated disturbances : IV (30 A/m (continuous)-300 A/m (1-3 s)) conforming to IEC 61000-4-8
 Surges immunity tests-conducted disturbances : III (2 kV CM, 1 kV DM) conforming to IEC 61000-4-5

climatic withstand	<p>Influence of corrosion/gaz test 2 (in operation) : 21 days, 75 % RH, 25 °C, 0.5 ppm H2S, 1 ppm SO2 conforming to IEC 60068-2-60 Influence of corrosion/gaz test 4 (in operation) : 21 days, 75 % RH, 25 °C, 0.01 ppm H2S, 0.2 ppm SO2, 0.2 ppm NO2, 0.01 ppm Cl2 conforming to IEC 60068-2-60 Continuous exposure to damp heat (in operation) : Cab : 10 days, 93 % RH, 40 °C conforming to IEC 60068-2-78 Continuous exposure to damp heat (in operation) : Cab : 10 days, 93 % RH, 40 °C conforming to IEC 60068-2-78 Continuous exposure to damp heat (in storage) : Cab : 56 days, 93 % RH, 40 °C conforming to IEC 60068-2-78 Continuous exposure to damp heat (in storage) : Db : 6 days, 95 % RH, 55 °C conforming to IEC 60068-2-30 Exposure to cold (in operation) : Ad : - 25 °C conforming to IEC 60068-2-1 Exposure to cold (in storage) : Ab : - 25 °C conforming to IEC 60068-2-1 Exposure to dry heat (in operation) : Bd : 70 °C conforming to IEC 60068-2-2 Exposure to dry heat (in storage) : Bb : 70 °C conforming to IEC 60068-2-2 Salt mist (in operation) : Kb/2 : 6 days conforming to IEC 60068-2-52 Temperature variation with specified variation rate (in storage) : Nb : - 25 °C to 70 °C, 5 °C/min conforming to IEC 60068-2-14</p>
ambient air temperature for operation	-25...70 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0925 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available