



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

## Part No: MC144WH

Description Stranded 21AWG PACW, 4C, PVC Insulation, PVC Sheath.

Applicable Standards AS/ACIF S008, BS4737-3.30

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as


Suitable Applications intercommunication.

Not suitable for mains connection.

### **Cable Construction Drawing**

#### **Cable Construction Relative Parts**











Cable Description									
Conductor	AWG	Stranding	Area(mm <sup>2</sup> )	Diameter(mm)	Material				
	21	14/0.2	0.44	0.87	PACW				
Insulation		: Thickness (mm OD (mm) :	, ,	PVC White, Blue, Red, Black : 0.3					
Sheath		: Thickness (mm OD (mm) :	PVC White n): 0.5 4.7						

With Garland, you are always well connected.







## Industrial / Power / Data / Security / Fibre

# Garland's Pro Series range is the experts' choice for high quality cables.

	1.5%							
Electrical Properties								
Voltage Rating			ELV					
Max. Conductor DC Resistance @ 20°C			45.2Ω/km					
Min. Insulation Resistance @ 20°C			50MΩ.km					
Voltage Test: Conductor to core			1.5 kV ac/1min					
Voltage Test: Core to sheath			3.0 kV ac/1min					
Mechanical Properties								
Operating Temperature Range			-15 to 70℃					
Max. Recommended Pulling Tension			123N					
Min. Bend Radius (install)			47mm					
Approximate Mass			3.4kg/100m					
Sheath Printing			GARLAND SECURITY CABLE MC144 - 4 x 14/0.20 22AWG - MM/YYYY - "Mmark"					
Supply Information								
Pack Size	Pack Type	Dimensio	ns	Qty Per Carton	Cartons Per Pallet			
100m	Plastic Reel	10 x 4.5 x	< 2.5"	6R	32			
250m	Wooden Reel	W24 x 21	.8cm	2R	64			
300m	Reel Box	14.5 x 14	.5 x 7.5"	1Box	45Box			
500m	Wooden Reel	W30 x 21	.8cm	1R	46			

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

