



### Main

Range	Acti 9
Product or component type	Fault contact
Device short name	ISD
Signal contacts composition	1 C/O
[Ie] rated operational current	3 A at 415 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC 6 A at 240 V AC - 50/60 Hz
9 mm pitches	1

### Complementary

[Ui] rated insulation voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Product weight	33 g
Colour	White
Connections - terminals	Screw clamp terminal 2 cable(s) 2.5 mm <sup>2</sup> rigid Screw clamp terminal 2 cable(s) 1.5 mm <sup>2</sup> flexible with cable end Screw clamp terminal 1 cable(s) 0.5...2.5 mm <sup>2</sup> flexible Screw clamp terminal 1 cable(s) 1...4 mm <sup>2</sup> rigid
Wire stripping length	10 mm
Tightening torque	1 N.m

### Environment

standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1
tropicalisation	2 conforming to EN/IEC 60947-5-1
relative humidity	95 % at 55 °C
ambient air temperature for operation	-35...70 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available