



### Main

Range of product	Acti 9
Range	Acti 9
Device short name	iATLc+s
Product or component type	Centralized control and remote indication auxiliary
Signal contacts composition	1 C/O
Signalling circuit voltage	24 V DC : 0.01...6 A 48 V DC : 0.01...2 A 130 V DC : 0.01...1 A 24...240 V AC : 50/60 Hz 0.01...6 A
Control circuit voltage	24...240 V AC 50/60 Hz

### Complementary

Mounting mode	Fixed, on right side of TL
Mounting support	DIN rail
Connections - terminals	Input connection : tunnel type terminals for 2 flexible cable(s) 2.5 mm <sup>2</sup> Input connection : tunnel type terminals for 2 rigid cable(s) 1.5 mm <sup>2</sup> Signalling circuit : tunnel type terminals for 2 flexible cable(s) 2.5 mm <sup>2</sup> Signalling circuit : tunnel type terminals for 2 rigid cable(s) 1.5 mm <sup>2</sup> Output connection : yellow clips
Product compatibility	ITL (16 A) ITL (32 A) ITLI ITLs
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White

### Environment

tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-20...50 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations