



### Main

Range of product	Acti 9
Range	Acti 9
Device short name	IATL4
Product or component type	Step by stel control auxiliary
Control circuit voltage	230 V AC 50/60 Hz impulse 50 ms

### Complementary

Remote control type	Push-button
Step sequences	1st impulse - TL1 on, TL2 off 2nd impulse - TL1 off, TL2 on 3rd impulse - TL1 on, TL2 on 4th impulse - TL1 off, TL2 off
Mounting mode	Fixed, between 2 TL
Mounting support	DIN rail
Connections - terminals	Input connection : tunnel type terminals for 2 flexible cable(s) 2.5 mm <sup>2</sup> Input connection : tunnel type terminals for 2 rigid cable(s) 1.5 mm <sup>2</sup> Signalling circuit : tunnel type terminals for 2 flexible cable(s) 2.5 mm <sup>2</sup> Signalling circuit : tunnel type terminals for 2 rigid cable(s) 1.5 mm <sup>2</sup> Output connection : yellow clips
Product compatibility	ITL (16 A) ITL (32 A) ITLI ITLc ITLs
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	69.5 mm
Colour	White

### Environment

tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-20...50 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.