

Product Environmental Profile

Acti 9 iATL24






General information

Representative product	Acti 9 iATL24 - A9C15424
Description of the product	Acti 9 iATL24 consists in 18 mm DIN mounted product to be associated to a contactor (Acti 9 ICT range) or an impulse relay (Acti 9 iTL range) with yellow clips which mechanically fixed the products together and feed, electrically speaking, the adjacent actuator.
Functional unit	The main purpose of iATL24 is to allows control and indication of a 230 V AC contactor or impulse relay from the Acti 9 Smartlink or by a PLC, by 24 V DC signals, it also allows control by a maintained/pulse signal. The reference lifetime of 10 years



Constituent materials

Reference product mass 77.95 g including the product, its packaging and additional elements and accessories



Plastics	44.8%
Metals	14.1%
Others	41.1%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>


Additional environmental information

The Acti 9 iATL24 presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 17.2 g, consisting of cardboard (60%), paper(40%)
Installation	Ref A9C15424 does not require any installation operations
Use	The product does not require special maintenance operations.
End of life	<p>End of life optimized to decrease the amount of waste and allow recovery of the product components and materials</p> <p>This product contains electronic card (13.7g) that should be separated from the stream of waste so as to optimize end-of-life treatment.</p> <p>The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website</p> <p>http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</p> <p>Recyclability potential: 61% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).</p>

Environmental impacts

Reference life time	10 years						
Product category	Other equipments - Active product						
Installation elements	No special components needed						
Use scenario	The product is in active mode 0.1% of the time with a power use of 18.4W and in Sleep mode 99.9% of the time with a power use of 0.8W for 10 years. And the duration of the operating modes expressed as a percentage of the full cycle time.						
Geographical representativeness	Europe						
Technological representativeness	Acti 9 iATL24 consists in 18 mm DIN mounted product to be associated to a contactor (Acti 9 iCT range) or an impulse relay (Acti 9 iTL range) with yellow clips which mechanically fixed the products together and feed, electrically speaking, the adjacent actuator.						
Energy model used	Manufacturing	Installation		Use		End of life	
	Energy model used: Spain	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27		Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27		Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	
Compulsory indicators		Acti 9 iATL24 - A9C15424					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	9.16E-04	9.13E-04	0*	0*	3.05E-06	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1.49E-01	2.78E-03	4.59E-05	0*	1.46E-01	2.32E-05
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	9.62E-03	7.62E-04	1.06E-05	0*	8.84E-03	9.51E-06
Contribution to global warming	kg CO ₂ eq	3.71E+01	2.00E+00	1.01E-02	0*	3.51E+01	2.67E-02
Contribution to ozone layer depletion	kg CFC11 eq	2.51E-06	2.26E-07	0*	0*	2.29E-06	9.81E-10
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	8.42E-03	3.75E-04	3.28E-06	0*	8.04E-03	2.12E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	1.27E+02	1.45E-02	0*	0*	1.27E+02	0*
Total Primary Energy	MJ	7.25E+02	2.36E+01	1.42E-01	0*	7.01E+02	1.05E-01



Optional indicators		Acti 9 iATL24 - A9C15424						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	4.16E+02	1.70E+01	1.41E-01	0*	3.98E+02	8.54E-02	
Contribution to air pollution	m³	1.72E+03	2.07E+02	4.28E-01	0*	1.51E+03	7.55E-01	
Contribution to water pollution	m³	1.75E+03	2.97E+02	1.65E+00	0*	1.45E+03	1.33E+00	
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Use of secondary material	kg	7.11E-04	7.11E-04	0*	0*	0*	0*	
Total use of renewable primary energy resources	MJ	8.99E+01	7.94E-01	0*	0*	8.91E+01	0*	
Total use of non-renewable primary energy resources	MJ	6.35E+02	2.28E+01	1.42E-01	0*	6.12E+02	1.05E-01	
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	8.96E+01	4.71E-01	0*	0*	8.91E+01	0*	
Use of renewable primary energy resources used as raw material	MJ	3.23E-01	3.23E-01	0*	0*	0*	0*	
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6.34E+02	2.18E+01	1.42E-01	0*	6.12E+02	1.05E-01	
Use of non renewable primary energy resources used as raw material	MJ	1.00E+00	1.00E+00	0*	0*	0*	0*	
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Hazardous waste disposed	kg	2.85E+00	2.74E+00	0*	0*	1.83E-02	9.47E-02	
Non hazardous waste disposed	kg	1.32E+02	8.62E-01	0*	0*	1.31E+02	0*	
Radioactive waste disposed	kg	8.77E-02	3.60E-04	0*	0*	8.74E-02	0*	
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Materials for recycling	kg	5.90E-02	6.16E-03	0*	1.72E-02	0*	3.57E-02	
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	
Materials for energy recovery	kg	6.56E-03	0*	0*	0*	0*	6.56E-03	
Exported Energy	MJ	5.45E-05	5.12E-06	0*	4.94E-05	0*	0*	

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	SCHN-00504-V01.01-EN	Drafting rules	PCR-ed3-EN-2015 04 02
Verifier accreditation N°	VH33	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Date of issue	12/2019	Information and reference documents	www.pep-ecopassport.org
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010			
Internal	External X		
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)			
PEP are compliant with XP C08-100-1 :2016			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »			



Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
 CS 30323
 F- 92506 Rueil Malmaison Cedex
 RCS Nanterre 954 503 439
 Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

SCHN-00504-V01.01-EN

© 2019 - Schneider Electric – All rights reserved

12/2019