



Main

Range of product	ICT
Device short name	iACTc
Product or component type	Double control input auxiliary
Control circuit voltage	24...48 V AC 50/60 Hz impulse 250 ms 24...48 V AC 50/60 Hz maintained
[Us] rated supply voltage	24...48 V AC 50/60 Hz

Complementary

Maximum output current	0.2 A holding 2 A inrush
Hold-in power consumption VA	3 VA
Mounting mode	Fixed, on the left of CT
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White
Connections - terminals	Input connection : tunnel type terminals for 2 flexible cable(s) 2.5 mm ² Input connection : tunnel type terminals for 2 rigid cable(s) 1.5 mm ² Output connection : yellow clips

Environment

ambient air temperature for operation	-20...60 °C
---------------------------------------	-------------

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1312 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.