



## Main

Range	Acti 9
Product name	Acti 9 iCT
Product or component type	Contactor
Device short name	ICT
Device application	Motor-heating-lighting
Poles description	2P
Pole contact composition	1 NO + 1 NC
Network type	AC
Utilisation category	AC-1 conforming to EN 60947-4-1 AC-3 conforming to EN 60947-4-1 AC-7A conforming to EN 61095 AC-7A conforming to IEC 1095 AC-7B conforming to EN 61095 AC-7B conforming to IEC 1095
Control type	Remote control
Control circuit voltage	230...240 V AC 50 Hz

## Complementary

[Ie] rated operational current	16 A AC-7A 6 A AC-7B
Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50 Hz
Maximum power	2.1 kW 250 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Control signal type	Maintained
Switching frequency	100 switching operations/day
Local signalling	Action indicator
Hold-in power consumption VA	3.8 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White
Electrical durability	200000 cycles AC 50/60 Hz conforming to EN 61095 200000 cycles AC 50/60 Hz conforming to IEC 1095
Connections - terminals	Control circuit : 2 tunnel type terminals 1.5 mm <sup>2</sup> for rigid cable(s) Control circuit : 2 tunnel type terminals 1.5 mm <sup>2</sup> for rigid cable(s) Power circuit : 1 tunnel type terminals 1...4 mm <sup>2</sup> for flexible cable(s) Power circuit : 1 tunnel type terminals 1.5...6 mm <sup>2</sup> for rigid cable(s) Control circuit : 1 tunnel type terminals 1.5...2.5 mm <sup>2</sup> for rigid cable(s) Control circuit : 2 tunnel type terminals 1.5...2.5 mm <sup>2</sup> for flexible cable(s)
Tightening torque	Control circuit : 0.8 N.m Power circuit : 0.8 N.m
Product compatibility	IACTs

## Environment

standards	EN 61095 IEC 1095
noise level	30 dB
heat dissipation	0.9 W at 50/60 Hz
IP degree of protection	IP20
pollution degree	2
tropicalisation	2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095
relative humidity	95 % (55 °C)
operating altitude	2000 m
ambient air temperature for operation	-5...60 °C
ambient air temperature for storage	-40...70 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations