

# A9C30215

impulse relay iTLI - 2P - 1NO+1NC - 16A - coil 24 VDC - 48 VAC 50/60Hz



## Main

Device application	Changeover relay
Range	Acti 9
Product name	Acti 9 iTL
Product or component type	Impulse relay
Device short name	ITLi
Poles description	2P
Pole contact composition	1 NO + 1 NC
[In] rated current	16 A
Network type	AC
Control circuit voltage	24 V DC 48 V AC 50/60 Hz 48 V AC 50/60 Hz

## Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V AC 50/60 Hz
Control type	Coil disconnection Remote and manual control
Control signal type	Impulse
Switching frequency	5 switching operations/minute 100 switching operations/day
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 3 mA
Local signalling	ON/OFF indication
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Height	84 mm
Width	18 mm
Depth	60 mm
Electrical durability	AC-22 : 100000 cycles AC-21 : 200000 cycles
Product compatibility	IATeT IATLc IATLc+s IETL iTL 16 IATL4 IATLm IATLs IATLz

## Environment

standards	EN 60947-1 EN 60947-2-2
product certifications	CCC GOST
quality labels	CEBEC IMQ KEMA NF

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

	VDE
noise level	<= 60 dB
tropicalisation	2
relative humidity	95 % ( 55 °C )
ambient air temperature for operation	-20...50 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1312 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations